

GENERAL LAWN NOTES

- CONTRACTOR SHALL COORDINATE OPERATIONS AND AVAILABILITY OF EXISTING TOPSOIL WITH ON-SITE CONSTRUCTION MANAGER
- LAWN AREAS SHALL BE LEFT 1" BELOW FINAL FINISHED GRADE PRIOR TO TOPSOIL INSTALLATION.
- CONTRACTOR TO FIND GRADE AREAS TO ACHIEVE FINAL CONTOURS AS SHOWN ON CIVIL DRAWINGS. POSITIVE DRAINAGE SHALL BE PROVIDED AWAY FROM ALL BUILDINGS. ROUNDING AT TOP AND BOTTOM OF SLOPES SHALL BE PROVIDED AND IN OTHER BREAKS IN GRADE. CORRECT AREAS WHERE STANDING WATER MAY OCCUR
- ALL LAWN AREAS SHALL BE FINE GRADED, IRRIGATION TRENCHES COMPLETELY SETTLED AND FINISH GRADE APPROVED BY THE OWNER'S CONSTRUCTION MANAGER OR LANDSCAPE ARCHITECT PRIOR TO LAWN INSTALLATION.
- CONTRACTOR SHALL REMOVE ALL ROCKS 3/4" IN DIAMETER AND LARGER. REMOVE ALL DIRT CLODS, STICKS, CONCRETE SPILLS, TRASH ETC PRIOR TO PLACING TOPSOIL AND GRASS INSTALLATION.
- CONTRACTOR SHALL MAINTAIN ALL LAWN AREAS UNTIL FINAL ACCEPTANCE.
- CONTRACTOR SHALL GUARANTEE ESTABLISHMENT OF ACCEPTABLE TURF AREA AND SHALL PROVIDE REPLACEMENT IF NECESSARY.

SOLID SOD:

- SOLID SOD SHALL BE PLACED ALONG ALL IMPERVIOUS EDGES, AT A MINIMUM. THIS SHALL INCLUDE CURBS, WALKS, INLETS, MANHOLES AND PLANTING BED AREAS. SOD SHALL COVER OTHER AREAS COMPLETELY AS INDICATED BY PLAN.
- SOD SHALL BE STRONGLY ROOTED DROUGHT RESISTANT SOD, NOT LESS THAN 2 YEARS OLD, FREE OF WEEDS AND UNDESIRABLE NATIVE GRASS AND MACHINE CUT TO PAD THICKNESS OF 3/4" (+1/4"), EXCLUDING TOP GROWTH AND THATCH.
- LAY SOD BY HAND TO COVER INDICATED AREAS COMPLETELY, ENSURING EDGES ARE TOUCHING WITH TIGHTLY FITTING JOINTS, NO OVERLAPS WITH STAGGERED STRIPS TO OFFSET JOINTS.
- TOP DRESS JOINTS IN SOD BY HAND WITH TOPSOIL TO FILL VOIDS IF NECESSARY.
- SOD SHALL BE ROLLED TO CREATE A SMOOTH EVEN SURFACE. SOD SHOULD BE WATERED THOROUGHLY DURING INSTALLATION PROCESS.
- SHOULD INSTALLATION OCCUR BETWEEN OCTOBER 1ST AND MARCH 1ST, OVERSEED BERMUDAGRASS SOD WITH WINTER RYEGRASS AT A RATE OF 4 POUNDS PER 1000 S.F.

HYDROMULCH:

- SCARIFY AND LOOSEN ALL AREAS TO BE HYDROMULCHED TO A MINIMUM DEPTH OF 4" PRIOR TO TOPSOIL AND HYDROMULCH INSTALLATION.
- BERMUDA GRASS SEED SHALL BE EXTRA HULLED, TREATED LAWN TYPE. SEED SHALL BE DELIVERED TO THE SITE IN ITS ORIGINAL UNOPENED CONTAINER AND SHALL MEET ALL STATE/LOCAL LAW REQUIREMENTS.
- FIBER SHALL BE 100% WOOD CELLULOSE FIBER, DELIVERED TO THE SITE IN ITS ORIGINAL UNOPENED CONTAINER AS MANUFACTURED BY "CONVEY" OR EQUAL.
- FIBER TACK SHALL BE DELIVERED TO THE SITE IN ITS UNOPENED CONTAINER AND SHALL BE "TERRO-TACK ONE", AS MANUFACTURED BY GROWERS, INC. OR APPROVED EQUAL.
- HYDROMULCH WITH BERMUDA GRASS SEED AT A RATE OF 2 POUNDS PER 1000 S.F.
- USE A BATTER BOARD AGAINST ALL BED AREAS TO PREVENT OVER SPRAY.
- IF INADEQUATE MOISTURE IS PRESENT IN SOIL, APPLY WATER AS NECESSARY FOR OPTIMUM MOISTURE FOR SEED APPLICATION.
- IF INSTALLATION OCCURS BETWEEN SEPTEMBER 1ST AND MAY 1ST, ALL HYDROMULCH AREAS SHALL BE OVER-SEED WITH WINTER RYE GRASS AT A RATE OF FOUR POUNDS PER ONE THOUSAND SQUARE FEET. CONTRACTOR SHALL BE REQUIRED TO RE-HYDROMULCH WITH BERMUDA GRASS THE FOLLOWING GROWING SEASON AS PART OF THIS CONTRACT.
- AFTER APPLICATION, NO EQUIPMENT SHALL OPERATE OVER APPLIED AREAS. WATER SEEDED AREAS IMMEDIATELY AFTER INSTALLATION TO SATURATION.
- ALL LAWN AREAS TO BE HYDROMULCHED SHALL ACHIEVE 100% COVERAGE PRIOR TO FINAL ACCEPTANCE.

LANDSCAPE NOTES

- CONTRACTOR TO VERIFY AND LOCATE ALL PROPOSED AND EXISTING ELEMENTS. NOTIFY LANDSCAPE ARCHITECT OR DESIGNATED REPRESENTATIVE FOR ANY LAYOUT DISCREPANCIES OR ANY CONDITION THAT WOULD PROHIBIT THE INSTALLATION AS SHOWN. SURVEY DATA OF EXISTING CONDITIONS WAS SUPPLIED BY OTHERS.
- CONTRACTOR SHALL CALL 811 TO VERIFY AND LOCATE ANY AND ALL UTILITIES ON SITE PRIOR TO COMMENCING WORK. LANDSCAPE ARCHITECT SHOULD BE NOTIFIED OF ANY CONFLICTS. CONTRACTOR TO EXERCISE EXTREME CAUTION WHEN WORKING NEAR UNDERGROUND UTILITIES.
- A MINIMUM OF 2% SLOPE SHALL BE PROVIDED AWAY FROM ALL STRUCTURES.
- CONTRACTOR SHALL FINE GRADE AREAS TO ACHIEVE FINAL CONTOURS AS INDICATED. LEAVE AREAS TO RECEIVE TOPSOIL 3" BELOW FINAL FINISHED GRADE IN PLANTING AREAS AND 1" BELOW FINAL FINISHED GRADE IN LAWN AREAS.
- LANDSCAPE ISLANDS SHALL BE CROWNED, AND UNIFORM THROUGHOUT THE SITE.
- PLANTING AREAS AND SOD TO BE SEPARATED BY STEEL EDGING. NO STEEL EDGING SHALL BE INSTALLED ADJACENT TO BUILDINGS, WALKS OR CURBS. EDGING NOT TO BE MORE THAN 1/2" ABOVE FINISHED GRADE. EDGING SHALL BE CUT AT 45 DEGREE ANGLE WHERE IT INTERSECTS WALKS AND/OR CURBS.
- MULCH SHALL BE INSTALLED AT 1/2" BELOW THE TOPS OF SIDEWALKS AND CURBING.
- QUANTITIES ON THESE PLANS ARE FOR REFERENCE ONLY. THE SPACING OF PLANTS SHOULD BE AS INDICATED ON PLANS OR OTHERWISE NOTED. ALL TREES AND SHRUBS SHALL BE PLANTED PER DETAIL.
- CONTRACTOR GROWN PLANT MATERIAL IS PREFERRED HOWEVER BALL AND BURLAP PLANT MATERIAL CAN BE SUBSTITUTED IF NEEDED AND IS APPROPRIATE TO THE SIZE AND QUALITY INDICATED ON THE PLANT MATERIAL LIST.
- TREES SHALL BE PLANTED AT A MINIMUM OF 5' FROM ANY UTILITY LINE, SIDEWALK OR CURB. TREES SHALL ALSO BE 10' CLEAR FROM FIRE HYDRANTS.
- 4" OF SHREDDED HARDWOOD MULCH (2" SETTLED THICKNESS) SHALL BE PLACED OVER WEED BARRIER FABRIC. MULCH SHALL BE SHREDDED HARDWOOD MULCH OR APPROVED EQUAL. PINE STRAW MULCH IS PROHIBITED.
- WEED BARRIER FABRIC SHALL BE USED IN PLANT BEDS AND AROUND ALL TREES AND SHALL BE MIRAF 1408 WEED BARRIER OR APPROVED EQUAL.
- CONTRACTOR TO PROVIDE UNIT PRICING OF LANDSCAPE MATERIALS AND BE RESPONSIBLE FOR OBTAINING ALL LANDSCAPE AND IRRIGATION PERMITS.

IRRIGATION:

- ALL REQUIRED LANDSCAPE AREAS SHALL HAVE AN AUTOMATIC IRRIGATION SYSTEM WITH A FREEZE/RAIN SENSOR. SYSTEM SHALL ALSO HAVE AN ET WEATHER BASED CONTROLLER AND BE DESIGNED AND INSTALLED BY A LICENSED IRRIGATOR.

MAINTENANCE REQUIREMENTS:

- VEGETATION SHOULD BE INSPECTED REGULARLY TO ENSURE THAT PLANT MATERIAL IS ESTABLISHING PROPERLY AND REMAINS IN A HEALTHY GROWING CONDITION APPROPRIATE FOR THE SEASON. IF DAMAGED OR REMOVED, PLANTS MUST BE REPLACED BY A SIMILAR VARIETY AND SIZE.
- MOWING, TRIMMING, EDGING AND SUPERVISION OF WATER APPLICATIONS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR UNTIL THE OWNER OR OWNER'S REPRESENTATIVE ACCEPTS AND ASSUMES REGULAR MAINTENANCE.
- ALL LANDSCAPE AREAS SHOULD BE CLEANED AND KEPT FREE OF TRASH, DEBRIS, WEEDS AND OTHER MATERIAL.

MISCELLANEOUS MATERIALS:

- STEEL EDGING SHALL BE 3/16" X 4 X 16' DARK GREEN DURADEGE STEEL. LANDSCAPE EDGING UNLESS NOTED OTHERWISE ON PLANS/DETAILS.
- DECOMPOSED GRANITE SHALL BE PLACED OVER WEED BARRIER FABRIC AND COMPACTED TO A 3" DEPTH.

CITY NOTES:

WARRANTY: THE OWNER, TENANT AND/OR THEIR AGENT, IF ANY, SHALL BE JOINTLY AND SEVERALLY RESPONSIBLE FOR THE MAINTENANCE OF ALL LANDSCAPING. ALL REQUIRED LANDSCAPING SHALL BE MAINTAINED IN A NEAT AND ORDERLY MANNER AT ALL TIMES. THIS SHALL INCLUDE, BUT NOT TO BE LIMITED TO, MOWING OF GRASS OF SIX INCHES (6") OR HIGHER, EDGING, PRUNING, FERTILIZING, WATERING, WEEDING, AND OTHER SUCH ACTIVITIES COMMON TO THE MAINTENANCE OF LANDSCAPING. LANDSCAPED AREAS SHALL BE KEPT FREE OF TRASH, LITTER, WEEDS, AND OTHER SUCH MATERIAL, OR PLANTS NOT A PART OF THE LANDSCAPING. ALL PLANT MATERIAL SHALL BE MAINTAINED IN A HEALTHY AND GROWING CONDITION AS IS APPROPRIATE FOR THE SEASON OF THE YEAR. PLANT MATERIAL WHICH DIES SHALL BE REPLACED WITH PLANT MATERIAL OF SIMILAR VARIETY AND SIZE, WITHIN NINETY (90) DAYS. TREES WITH A TRUNK DIAMETER IN EXCESS OF SIX INCHES (6") MEASURED TWENTY-FOUR INCHES (24") ABOVE THE GROUND MAY BE REPLACED WITH ONES OF SIMILAR VARIETY HAVING A TRUNK DIAMETER OF NO LESS THAN THREE INCHES (3") MEASURED TWENTY-FOUR INCHES (24") ABOVE THE GROUND. A TIME EXTENSION MAY BE GRANTED BY THE PLANNING MANAGER IF SUBSTANTIAL EVIDENCE IS PRESENTED TO INDICATE ABNORMAL CIRCUMSTANCES BEYOND THE CONTROL OF THE OWNER OR HIS AGENT. FAILURE TO MAINTAIN ANY LANDSCAPE AREA IN COMPLIANCE WITH THIS SECTION SHALL RESULT IN THE DISAPPROVAL AND REVOCATION OF ANY ISSUED CERTIFICATE OF OCCUPANCY ASSOCIATED WITH THE OCCUPANCY OF SAID AREA.


GENERAL STANDARDS

- ALL REQUIRED LANDSCAPED OPEN AREAS SHALL BE COMPLETELY COVERED WITH LIVING PLANT MATERIAL. ARTIFICIAL LANDSCAPING MATERIALS SUCH AS WOOD CHIPS AND GRAVEL, MAY BE USED UNDER TREES, SHRUBS AND OTHER PLANTS.
- PLANT MATERIALS SHALL CONFORM TO THE STANDARDS OF THE RECOMMENDED PLANT LIST FOR THE CITY OF KELLER (SEE ARTICLE NINE - RECOMMENDED LIST FOR REQUIRED LANDSCAPE AREAS). GRASS SEED, SOD AND OTHER MATERIAL SHALL BE CLEAN AND REASONABLY FREE OF WEEDS AND NOXIOUS PESTS AND INSECTS.
- GRASS AREAS SHALL BE SODDED, PLUGGED, SPRIGGED, HYDRO-MULCHED OR SEEDED EXCEPT THAT SOLID SOD SHALL BE USED IN SWALES, EARTHEN BERMS OR OTHER AREAS SUBJECT TO EROSION.
- GROUND COVERS USED IN LIEU OF GRASS IN WHOLE AND IN PART SHALL BE PLANTED IN SUCH A MANNER AS TO PRESENT A FINISHED APPEARANCE AND REASONABLY COMPLETED COVERAGE WITHIN ONE (1) YEAR OF PLANTING.
- ALL REQUIRED LANDSCAPED OPEN AREAS SHALL BE PROVIDED WITH ADEQUATE AND INCONSPICUOUS IRRIGATION SYSTEMS.
- EARTHEN BERMS SHALL HAVE SIDE SLOPES NOT TO EXCEED 33.3 PERCENT (THREE FEET (3') OF HORIZONTAL DISTANCE FOR EACH ONE FOOT (1') OF HEIGHT). ALL BERMS SHALL CONTAIN NECESSARY DRAINAGE PROVISIONS AS MAY BE REQUIRED BY THE CITY ENGINEER.
- SMALL SHRUBS SHALL BE TRIMMED TO A HEIGHT NO GREATER THAN THREE FEET (3'). ORNAMENTAL TREES SHALL BE TRIMMED FROM THE BASE UP TO A MINIMUM HEIGHT OF THREE FEET (3').

LANDSCAPE TABULATIONS for Keller, Texas	
BUFFER TREES	
1. One large canopy tree (3" caliper) no more than 60' apart on all other required buffers.	
REQUIRED	PROVIDED
2 trees, 3" cal.	2 trees, 3" cal.
PARKING LOTS	
1. Parking lots shall be 100% screened with shrubs or berms adjacent to all public streets.	
2. All parking lot islands must contain one large 3" caliper canopy tree.	
3. A minimum of 15% of all parking lots shall be landscaped.	
4. Foundation planting a minimum of 5' in width shall be provided at the fronts and sides of buildings and consist of a combination of groundcovers, shrubs, and ornamental trees.	
REQUIRED	PROVIDED
parking lot screen, 3' ht.	NA
2 trees, 3" cal.	2 trees, ornamental due to overhead lines
102 s.f. (15%)	471 s.f.
foundation planting	foundation planting

PLANT SCHEDULE				
QTY	LABEL	COMMON NAME	SCIENTIFIC NAME	SIZE NOTES
SHADE TREES				
2	RO	Texas Red Oak	<i>Quercus texana</i>	3" cal. 12' ht., 4' spread, matching
ORNAMENTAL TREES				
2	MP	Mexican Plum	<i>Prunus mexicana</i>	30 gal. 8' ht., 4' spread min.
SHRUBS				
10	AB	Abelia 'Little Richard	<i>Abelia x grandiflora 'Little Richard'</i>	5 gal. full, 20" spread, 30" o.c.
14	DY	Dwarf Yaupon Holly	<i>Ilex vomitoria 'Condeaux'</i>	5 gal. full, 24" sprd, 24" o.c.
5	LS	Little Princess Spirea	<i>Spiraea japonica 'Little Princess'</i>	5 gal. full, 20" sprd, 24" o.c.
GROUNDCOVER/VINES/GRASS				
15	AJ	Asian Jasmine	<i>Trachelosperum asiaticum</i>	1 gal. full, 12" o.c.
45	DL	Daylily / Giant Liriope	<i>Hemerocallis Stella de Oro/ Liriope gigantea</i>	1 gal. full, 18" o.c.
		Bermuda Solid Sod	<i>Cynodon dactylon</i>	
		Decomposed Granite		

Plant list is an aid to bidders only. Contractor shall verify all quantities on plan. All heights and spreads are minimums. Trees shall have a strong central leader and be of matching specimens. All plant material shall meet or exceed remarks as indicated.



AWR Designs, LLC
P.O. Box 1746
Aledo, Texas 76008
amanda@awr-designs.com
c. 512.517.5589

REVISION NUMBER	REVISION DATE	DESCRIPTION

Lobinger & Potts Structural Engineering, Inc
The Colony, Texas 75056
PO Box 560215
817.488.9933
Firm Reg. #7290

116 TAYLOR STREET
KELLER, TX

LANDSCAPE PLAN

PROJECT #	
MANAGER	LPSE
DRAWN BY	LPSE
ISSUED FOR	
DATE	5/12/2025



SHEET

L-1.1

