CIVIL CONSTRUCTION PLANS GRADING, EROSION CONTROL, AND TREE PROTECTION FOR

MARSHALL RIDGE PHASE 1 - SOUTH


LOTS 19-21 & 23, BLOCK D LOTS 2-3 & 17-19, BLOCK G CITY OF KELLER, TARRANT COUNTY, TEXAS



13455 NOEL ROAD STATE OF TEXAS
TWO GALLERIA OFFICE TOWER,
SUITE 700
DALLAS, TEXAS 75251
TEL: (972) 770-1300
CONTACT: BRYAN R. MOODY, P.E.

OWNER/DEVELOPER

MERITAGE HOMES OF TEXAS, LLC 8840 CYPRESS WATERS BLVD IRVING, TEXAS 75019 TEL: (972) 580-6300 CONTACT: DAVID AUGHINBAUGH



VICINITY MAP


SCALE: 1" = 1,000'





FEBRUARY 2019


SHEET INDEX SHEET NO. DESCRIPTION C-01 COVER SHEET C-02 RECORDED FINAL PLAT - BY OTHERS C-03 RECORDED FINAL PLAT - BY OTHERS C-04 GRADING PLAN C-05 GRADING PLAN


EROSION CONTROL & TREE PRESERVATION PLAN
EROSION CONTROL & TREE PRESERVATION DETAILS











C-06


TALL FESCUE

*USE ONLY USDA CERTIFIED SEED.

SANITARY SEWER EFFLUENT IS DISPOSED OF VIA AN ONSITE SEWER SYSTEM CONNECTED TO A MUNICIPAL SEWER SYSTEM.

9/1 - 10/15

7#-10#/1000 SF



DAMAGE TO THE CROWN, TRUNK OR ROOT SYSTEM IMMEDIATELY. - REPAIR ROOTS BY CUTTING OFF THE DAMAGED AREAS AND PAINTING THEM WITH TREE PAINT. SPREAD PEAT MOSS OR MOIST TOPSOIL OVER EXPOSED ROOTS. - REPAIR DAMAGE TO BARK BY TRIMMING AROUND THE DAMAGED AREAS, TAPER THE CUT TO PROVIDE DRAINAGE, AND PAINT WITH TREE PAINT. - CUT OFF ALL DAMAGED TREE LIMBS ABOVE THE TREE COLLAR AT THE TRUNK OR MAIN BRANCH. USE THREE SEPARATE CUTS TO AVOID PEELING BARK FROM HEALTHY AREAS OF THE TREE.


NOTES: IN SPITE OF PRECAUTIONS, SOME DAMAGE TO PROTECTED TREES MAY OCCUR. IN SUCH CASES REPAIR ANY

(CX) <u>EROSION CONTROL MATTING (CURLEX)</u>

-STAPLE OR STAKE AS PER MFG. RECOMMENDATIONS (TYP.) SECTION A-A TYPICAL JOINT OVERLAP

UPSTREAM ANCHORING

-EROSION CONTROL MATTING



STABILIZED CONSTRUCTION ENTRANCE

EXISTING GRADE

REVISION DATE: 9/14/2009 SHEET: E-5

EMBEDMENT = 1'

WIRE MESH - BACKING SUPPORT

FABRIC TOE-IN

REVISION DATE:

2/11/2009

SHEET: E-01

4x4-W1.4xW1.4 MINIMUM ALLOWABLE, TYP. CHAIN LINK FENCE FABRIC IS

EROSION CONTROL DETAILS

LENGTH AS SHOWN ON PLANS

REVISION DATE 2/11/2009 SHEET: E-03

- FILTER FABRIC

PAVED SURFACE --/

PROFILE VIEW

TRANSITION TO PAVED SURFACE—

PLAN VIEW N.T.S.

DRAINAGE MUST FLOW

EROSION CONTROL DETAILS RESIDENTIAL SITE EROSION CONTROL

> SILT FENCE -(MIN. HEIGHT 24" ABOVE EXIST. GROUND)

COMPACTED EARTH -

HAYLI ST.

4'-0" SIDEWALI

ALT PROPOSED DRIVEWAY

STAKED HAY BALES

STABILIZED CONSTRUCTION ENTRANCE GENERAL NOTES:

CASES SHALL BE 50 FEET.

POINTS OF INGRESS OR EGRESS.

WATERCOURSE USING APPROVED METHODS.

1. STONE SHALL BE 3 TO 5 INCH DIAMETER CRUSHED ROCK OR ACCEPTABLE CRUSHED PORTLAND CEMENT CONCRETE.

2. LENGTH SHALL BE SHOWN ON PLANS, WITH A MINIMUM LENGTH OF 30 FEET FOR LOTS WHICH ARE LESS THAN 150 FEET FROM EDGE OF PAVEMENT. THE MINIMUM DEPTH IN ALL OTHER

4. THE WIDTH SHALL BE NO LESS THAN THE FULL WIDTH OF ALL

5. WHEN NECESSARY, VEHICLES SHALL BE CLEANED TO REMOVE SEDIMENT PRIOR TO ENTRANCE ONTO A PUBLIC ROADWAY. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH CRUSHED STONE WITH DRAINAGE FLOWING AWAY FROM BOTH THE STREET AND THE STABILIZED ENTRANCE. ALL SEDIMENT SHALL BE PREVENTED FROM ENTERING ANY STORM DRAIN, DITCH OR WATERCOLUSE LISING APPROVED METHODS

6. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING SEDIMENT ONTO PAVED

SURFACES. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND. ALL SEDIMENT SPILLED, DROPPED, WASHED, OR TRACKED ONTO PAVED SURFACES MUST BE REMOVED IMMEDIATELY.

7. THE ENTRANCE MUST BE PROPERLY GRADED OR INCORPORATE A DRAINAGE SWALE TO PREVENT RUNOFF FROM LEAVING THE CONSTRUCTION SITE.

3. THE THICKNESS SHALL NOT BE LESS THAN 6 INCHES.

SILT FENCE GENERAL NOTES:

DEVICE IS EMPLOYED.

POSTS WHICH SUPPORT THE SILT FENCE SHALL BE INSTALLED ON A SLIGHT ANGLE TOWARD THE ANTICIPATED RUNOFF SOURCE. POST MUST BE EMBEDDED A MINIMUM OF ONE FOOT.

2. THE TOE OF THE SILT FENCE SHALL BE TRENCHED IN WITH A SPADE OR MECHANICAL TRENCHER, SO THAT THE DOWN SLOPE FACE OF THE TRENCH IS FLAT AND PERPENDICULAR TO THE LINE OF FLOW. WHERE FENCE CANNOT BE TRENCHED IN (e.g. PAVEMENT), WEIGHT FABRIC FLAP WITH ROCK ON UPHILL SIDE TO PREVENT FLOW FROM SEEPING UNDER FENCE.

3. THE TRENCH MUST BE A MINIMUM OF 6 INCHES DEEP AND 6 INCHES WIDE TO ALLOW FOR THE SILT FABRIC TO BE LAID IN THE GROUND AND BACK FILLED WITH COMPACTED

4. SILT FENCE SHOULD BE SECURELY FASTENED TO EACH SUPPORT POST OR TO WIRE BACKING, WHICH IN TURN IS ATTACHED TO THE FENCE POST. THERE SHALL BE A 3 FOOT OVERLAP, SECURELY FASTENED WHERE ENDS OF FABRIC MEET.

5. INSPECTION SHALL BE AS SPECIFIED IN THE SWPPP. REPAIR OR REPLACEMENT SHALL BE MADE PROMPTLY AS NEEDED.

6. SILT FENCE SHALL BE REMOVED WHEN FINAL STABILIZATION IS ACHIEVED OR ANOTHER EROSION OR SEDIMENT CONTROL

7. ACCUMULATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF HALF THE HEIGHT OF THE FENCE. THE SILT SHALL BE DISPOSED OF AT AN APPROVED SITE AND IN SUCH A MANNER AS NOT TO CONTRIBUTE TO ADDITION SILTATION.

NOTE: TEMPORARY DRIVE AND CONSTRUCTION ENTRANCE PLACED BEFORE CONSTRUCTION STARTS.

SILT FENCE TO BE PLACED AT BACK OF ALL CURBS, DRAINAGE DITCHES, COMMON SIDE YARD SWELLS, AND DOWN HILL SLOPES @ PROPERTY LINES.

HAY BALES AROUND DROP INLET. ~ STAKED AT EDGE OF APRON.

PROPOSED GARAGE

PROPOSED HOUSE PAD

23 ∞ ⊢

BLOCK (RO PRI

SHEET NUMBER

C-07

REVISION DATE EROSION CONTROL DETAILS EROSION CONTROL DETAILS 9/14/2009 **INLET PROTECTION** SILT FENCE STRUCTURES SHEET: E-04

