

CE - #515-16, GM - #529-17

SVL95-2SHFC WEB QUOTE #1490410

Date: 10/26/2019 6:26:24 AM -- Customer Information --Bailey, Bobby City of Keller bbailey@cityofkeller.com 817-743-4251

Quote Provided By

Zimmerer Kubota & Equipment, Inc.

Steve Lee

5165 Mark IV Parkway Ft. Worth, TX 76106 email: stevel@zkmail.com phone: 8172816143

-- Custom Options --



S Series

SVL95-2SHFC

-- Standard Features --

* * * EQUIPMENT IN STANDARD MACHINE * * *

FFATURES

Final Tier 4 Certified Kubota Diesel Engine Electronic Travel Torque Management System Vertical Lift Path Loader Frame High Flow Auxiliary Hydraulics Standard Front Quick Coupler, Float Standard

Hydraulic Quick Coupler Option DIMENSIONS Loader Arm Self-Leveling Loader Boom Lock Open ROPS/FOPS Optional enclosed and pressurized cab with A/C High Back, Adjustable, Vinyl,

Suspension Seat 2" Retractable Seat Belt And 2-Piece Seat Bar

23.1 gpm Auxiliary Hydraulics Standard, 40.0 gpm Option Direct To Tank Return Line Rigid Mounted Undercarriage, 5 Lower Track Rollers

High Grip Rubber Tracks, 17.7" Standard

Two Speed Travel System Automatic Wet Disk Parking Brake

Kubota 4 Hydraulic Pump Load Sensing System

3 Variable Displacement Pumps,

1 additional piston pump for **High Flow Option** Hydraulic Joystick Controls ISO Operating Pattern Dial Knob And Foot Throttle Controls

Stall Guard Engine Control Automatic Glow Plugs Key Switch Stop System Self Bleed Fuel System 2 Front And 2 Rear Working Lights

Hour Meter, Engine Temperature, DEF, And Fuel Gauges And Warning Lights Horn And Backup Alarm Lockable DEF Tank Cap Lockable Fuel Cap Radio Ready on Enclosed Cabs

BASIC UNITS

SVL95-2SHFC, 17.7" Rubber Tracks. A/C ROPS/FOPS Cab Hydraulic Quick Coupler,

OPERATIONAL

Operating Weight*, SVL95-2s, 17.7" Rubber Tracks, Open ROPS/FOPS Cab, Mechanical Quick Coupler 11,299 lbs.

Rated Operating Capacity (ROC) @ 35%

of Tipping Load complies with ISO 14397-1

and SAE J 818) 3.200 lbs. Rated Operating Capacity (ROC)

@ 50% of Tipping Load 4,572 lbs. Tipping Load 9,143 lbs.

Auxiliary Hydraulics Flow 23.1 / 40.0 gpm

Travel Speed (Low / High) 5.0 / 7.3 mph

Reach @ Maximum Height 40.7" Height to Hinge Pin 128.6" Ground Pressure 4.4 psi. Traction Force 12,178 lbf.

* Includes operator's weight, 175

ENGINE

V3800-Tier 4 Kubota Final Tier 4 Diesel Engine 4 Cylinder, 4 Cycle, Turbo Charged 96.0 Gross HP @ 2400 rpm

DIMENSIONS

Cab Height 83 4" Width (without attachment) 77.2" Length (without attachment) 123.5" Length of Track on Ground 65.6"

SVL95-2SHFC Base Price: \$82,047.00 (1) 80" HEAVY DUTY HIGH CAPACITY BUCKET \$1,873.00

(25 CU-FT) W/CUTTING EDGE

AP-HD80HC-80" HEAVY DUTY HIGH CAPACITY BUCKET (25

CU-FT) W/CUTTING EDGE

(1) REAR VIEW MIRROR KIT \$22.00 S6641-REAR VIEW MIRROR KIT

(1) HOSE STAY S6689-HOSE STAY

\$98.00 \$84,040.00

Configured Price: BUY BOARD Discount: (\$20,169.60)

SUBTOTAL: \$63,870.40 Dealer Assembly: \$34.00

Freight Cost: \$665.00

PDI: \$250.00 AP-TR48-11-38-61-70 quote 1912 \$7,172.50

AP-SGC2084-11 quote 1924 \$4,403.00

Trade in equipment (\$53,500.00)

Total Unit Price: \$22,894.90

Quantity Ordered:

Final Sales Price: \$22.894.90

Purchase Order Must Reflect the Final Sales Price

To order equipment – purchase orders must be made out and

Kubota Tractor Corporation Attn: National Accounts 1000 Kubota Drive Grapevine, TX 76051

or email NA.Support@kubota.com or call 817-756-1171 or fax 844-582-1581

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability